



Rating @ 0.8 PF		Prime rating	Stand-by rating
Voltage ^{*1}	Freq. ^{*2}	RM135 ^{*3}	RM150S ^{*4}
400 V	50 Hz	135.0 KVA	150.0 KVA
480 V	60 Hz	153.6 KVA	167.9 KVA

RM135 - RM150 S

RM135 - RM150S SB issue B2012

The above ratings represent the generating set capability guaranteed within $\pm 3\%$ at the reference conditions equivalent to those specified in ISO 8528/1, ISO 3046/1 and BS 5514/1

NOTES

- 1 - The applicable voltage range is 380V to 415V for 50Hz applications and 380V to 480V for 60Hz applications.
- 2 - This generating set is of switchable speed of 1500rpm/1800rpm.
- 3 - RM135 is the prime power rating of the generating set, where a variable load and unlimited hours usage are applied on the generating set with an average load factor of 80% of the prime rating over each 24 hour period. Noting that a 10% overload is available for 1 hour in every 12 hours operation.
- 4 - RM150S is the standby power rating of the generating set, where a variable load limited to an annual usage up to 500 hours is applied, with 300 hours of which may be continuous running. Noting that no overload is permitted.

Engine Technical Data

Model	Perkins 1006TAG	
Cylinders	6; vertical in-line	
Aspiration	Turbocharged	
Combustion	Direct injection	
Cooling System	Water cooled	
Displacement	5.99 L	
Oil consumption	0.2 % of fuel consumption	
Lube oil capacity	19 L	
Coolant capacity	37.22 L	
Governor	Electronic	
Emissions regulations	Non-compliant	
Speed	1500 rpm	1800 rpm
Fuel Consumption PT135	31.5 L/H	37.6 L/H
Fuel Consumption PT150S	34.6 L/H	41.3 L/H
Radiator Cooling Air Flow	154 m ³ /min	182 m ³ /min
Max Exhaust Gas Flow	24.1 m ³ /min	29.7 m ³ /min

The above performance data are valid as per the following specs:

- Diesel Fuel is according to BS2869 Class A2 or equivalent.
- Lubricating oil is according to API CH4 (15W/40).
- The coolant should be 50% antifreeze and 50% fresh water.

Alternator Technical Data

Model	Leroy Somer LSA 44.2 S75		
Regulation	$\pm 0.5\%$		
International protection	IP23		
Insulation class	H		
Terminals	12		
Frequency	50 Hz	60 Hz	
Coolant Air Flow	0.37 m ³ /s	0.44 m ³ /s	

Shipping Data

Length	Width	Height	Weight
2500 mm	770 mm	1350 mm	1250 kg

RICH MOTOR COMPANY (FZE)
HAMRIAH FREEZONE - SHARJAH (PHASE II)
UNITED ARAB EMIRATES

Mob: +971 50 978 8830
Tel: +971 6 748 9001
Fax: +971 50 269 4033

e-mail: rmcghaddar@gmail.com
www.richmotor.com

