



Rating @ 0.8 PF		Prime rating	Stand-by rating
Voltage ^{*1}	Freq. ^{*2}	RM2000 ^{*3}	RM2200S ^{*4}
400 V	50 Hz	2000 KVA	2200 KVA
480 V	60 Hz	-	-

RM2000 - RM2200 S

RM2000 - RM2000S SB issue B2012

The above ratings represent the generating set capability guaranteed within $\pm 3\%$ at the references conditions equivalent to those specified in ISO 8528/1, ISO 3046/1 and BS 5514/1

NOTES

- 1 - The applicable voltage range is 380V to 415V for 50Hz applications and 380V to 480V for 60Hz applications.
- 2 - This generating set is of fixed speed of 1500rpm.
- 3 - RM2000 is the prime power rating of the generating set, where a variable load and unlimited hours usage are applied on the generating set with an average load factor of 80% of the prime rating over each 24 hour period. Noting that a 10% overload is available for 1 hour in every 12 hours operation.
- 4 - RM2200S is the standby power rating of the generating set, where a variable load limited to an annual usage up to 500 hours is applied, with 300 hours of which may be continuous running. Noting that no overload is permitted.

The above performance data are valid as per the following specs:

- Diesel Fuel is according to BS2869 Class A2 or equivalent.
- Lubricating oil is according to API CH4 (15W/40).
- The coolant should be 50% antifreeze and 50% fresh water.

Engine Technical Data

Model	Perkins 4016-61TRG2	
Cylinders	16;60 Vee Form	
Aspiration	Turbocharged & A/A charge cooled	
Combustion	Direct injection	
Cooling System	Water cooled	
Displacement	61.123 L	
Oil consumption	0.52 g/KW hr	
Lube oil capacity	237 L	
Coolant capacity	316 L	
Governor	Electronic	
Emissions regulations	TA-Luft(1986)	
Speed	1500 rpm	1800 rpm
Fuel Consumption PT2000	436.0 L/H	-
Fuel Consumption PT2200S	490.0 L/H	-
Radiator Cooling Air Flow	2058 m ³ /min	-
Max Exhaust Gas Flow	395 m ³ /min	-

Alternator Technical Data

Model	Leroy Somer LSA 50.1 M60	
Regulation	$\pm 0.5\%$	
International protection	IP21	
Insulation class	H	
Terminals	6	
Frequency	50 Hz	60 Hz
Coolant Air Flow	2.5 m ³ /s	-

Shipping Data

Length	Width	Height	Weight
5700 mm	2780 mm	3540 mm	15100 kg

RICH MOTOR COMPANY (FZE)
HAMRIAH FREEZONE - SHARJAH (PHASE II)
UNITED ARAB EMIRATES

Mob: +971 50 978 8830
Tel: +971 6 748 9001
Fax: +971 50 269 4033

e-mail: rmcghaddar@gmail.com
www.richmotor.com

