



The lighting tower of the new family Night Pro 4000 stands out by its functional and easy use.

The Night Pro guarantees a continuous work during 20 hours per fuel tank providing the highest performance. The new family of lighting towers includes an innovative design and responds to strict security, portability, maintenance and versatility standards.

RICH MOTOR COMPANY (FZE ) HAMRIAH FREEZONE - SHARJAH ( PHASE UNITED ARAB EMIRATES

Tel: +971 6 5269111 Fax: +971 6 5269431

e-mail:sales@richmotor.com

www.richmotor.com

## Night Pro 4000 RANGE



**Events** 



**Road Works** 



**Construction Sites** 



Industry



Rental




Mining












Its design and reduced dimensions make the product easy to move, storing up to 14 units in a 40 foot container.


These features make the lighting tower perfect for the construction, pleasure, events, civil defence, emergency and fire brigades sectors among others.

Perkins UK

	Perkills OK			
Lighting tower model		Night-Pro 4000-P		
(P.R.P) Power				
Frequency Switchable 50 -60Hz	Hz	50/60	50/60	50/60
Voltage	V	230	230	230
Maximum dimensions				
(working mode)		2430mm(L)x2000mm(W)x9000mm(H)		
Minimum dimensions				
(transport mode)		3700mm(L)x1420mm(W)x1800mm(H)		
Weight unfuelled	Kg	934	974	1074
Fuel		Diesel		
Tank capacity	L	50		
Maximum run time	Hr	16	10	9.4
ENGINE		Perkins	Perkins	Perkins
Model		403A-11G1	403A-15G1	404A-22G1
Cylinders		3 Cyl	3 Cyl	4 Cyl
Aspiration		Natural		
Rated speed		1500/1800		
Cooling system		Water Cooled		
Fuel consumption (100% load)		3 L/Hr	5 L/Hr	5.3 L/Hr
Speed governor		Mech		

ALTERNATOR		Leroy Somer(Fr) or Linz(It)			
Model		40 VS1	40 VS2	40M5	
		or	or	or	
		E1X13S/4	E1X13M/4	PRO18S A/4	
Poles nº		4			
FEATURES					
Rotation		360⁰			
Lamps nº		4 x 1000 W			
Lamps type		Metal Halide or Hallogene			
Total lumens		360,000 / 210,000			
Light field		38	00m <sub>2</sub> / 30	000m <sub>2</sub>	
Auxiliary sockets		2x16Amps			
Tyres		2 x 165R13			
Stabilisers		4			
Fork pockets		Standard			







Tel: +971 6 748 9001 Fax: +971 50 269 4033

e-mail:sales@richmotor.com

www.richmotor.com



